

Standard Features

P61 Purifier with Refillable Purifier Element (Stainless steel)

High Pressure Particle and Oil Removel Filter (Stainless Steel)

2nd and 3rd stages Water Seperator (Stainless Steel)

Intercoolers (Stainless Steel) Aftercooler (Stainless Steel)

Priority Valve (Pressure Maintaining Valve)

Check Valve

Electric Panel: Y∆ starter

Canopy Isolated from Subbase for Smoothest Operation

Auto Drain

Automatic Start/Stop

Oil Level Switch

Removable Filling Panel with 4 Filling Hoses (Yokes, Filling Valves) and Cylinder Pressure Gauge

Control Panel: 4 Stage Pressure Gauges, Main Switch, On/Off Buttons, Hourmeter, Test, Reset and Emergency Pushbuttons , 5 Control Leds

Tropical Cooling with Electric Ventilation Fans

Air Quality comply with EN 12021

Optional Features

Extra Filling Hoses
Dual Pressure Systems 225-310 Bar/3260-4500 Psi
Disposable Fitler Cartridge
Electronic Control System

ALKIN Modello	Working Pressure		Displacement Capacity			Motor Power		RPM	Stages	Cylinders	Weight	Dimensions(cm)		
	Bar	Psi	Lt/min	m³/h	Cfm	НР	KW					w	L	н
	225/310	3260/4500	450	28,8	16,9	10	7,5	550	4	3	730			
W4	225/310	3260/4500	600	36	21,2	15	11	720	4	3	740			
Canopy	225/310	3260/4500	685	41,1	24,2	20	15	830	4	3	750	77	111	164
	415	6000	530	31,8	18,7	15	11	640	4	3	790			
	415	6000	600	36	21,2	20	15	720	4	3	800			

Please note that information and pictures may be changed or updated without notice, at any time.



Sectors

Scuba Diving
Fire Brigades
Military
Applications
Naval
Applications
Fish Farms
Gas Filling Facilities



