

# W32

## ENCLOSED

### Standard Features

- P41 Purifier with Refillable Purifier element (Stainless steel)
- 2nd Stages Water Separator
- Prefilter (Acting as a 3rd stage water separator)
- Intercoolers (Stainless Steel)
- Aftercooler (Stainless Steel)
- Priority Valve (Pressure Maintaining Valve)
- Check Valve
- Pressure Switch for Automatic Start/Stop
- Oil Pressure Switch
- Auto Drain
- Interlocked Filling Panel with 2 filling Hoses ( Yokes, Filling Valves)
- Control Panel: 2 Pressure Gauges for cylinders charge, Oil Pressure Gauge and Purifier Pressure Gauge
- Electric Panel :YΔ Starter, Main Switch, On/Off Buttons, Hourmeter, Emergency Pushbuttons
- Air Quality comply with EN 12021



### Optional Features

- Extra Filling Hoses
- Dual Pressure Systems 225-310 Bar/3260-4500 Psi
- Disposable Filter Cartridge
- Electronic Control System

### Sectors

- Scuba Diving
- Fire Brigades
- Military Applications
- Naval Applications
- Fish Farms
- Gas Filling Facilities
- Marine

ALKIN Model	Working Pressure		Displacement Capacity			Motor Power		RPM	Stages	Cylinders	Kg.	Dimensions (cm)		
	Bar	Psi	Lt/min	m <sup>3</sup> /h	Cfm	HP	KW					W	L	H
W32 Enclosed Three Phase	225/310	3260/4500	170	10,2	6	5,5	4	1300	3	3	220	55	100	89
	225/310	3260/4500	240	14,4	8,4	7,5	5,5	1500	3	3	250	55	100	89
	225/310	3260/4500	300	18	11	10	7,5	1700	3	3	260	55	100	89

Please note that information and pictures may be changed or updated without notice, at any time.