

## Standard Features

P21 vith Refillable Purider Elelment for FAD upto 170 lt/min

P41 Purifier (stainless steel) with Refillable Purifier Element (stainless steel) for FAD higher than 170 lt/min

2nd and 3rd stage Water Seperator

Intercoolers (Stainless Steel)

Aftercooler (Stainless Steel)

Priority Valve (Pressure Maintaining Valve)

Check Valve

Manual Drain

Manual Start-Stop

2 Filling Hose (Yoke, Filling Valve, Pressure Gauge, DIN Adapter)

Air Quality comply with EN 12021

## **Optional Features**

Automatic Start/Stop Auto Drain

Diesel Engine: manual or electric start

Extra Filling Hoses

Dual Pressure Systems 225-310 Bar / 3260-4500 Psi

Disposable Fitler Cartridge





	ALKIN Model	Working Pressure		Displacement Capacity			Motor Power		RPM	Stages	Cylinders	Kg.	Dimensions (cm)		
		Bar	Psi	Lt/min	m³/h	Cfm	НР	KW					w	L	н
V	W32 Meriner Three Phase	225/310	3260/4500	170	10,2	6	5,5	4	1300	3	3	130	56	112	57
		225/310	3260/4500	240	14,4	8,4	7,5	5,5	1500	3	3	165	56	112	71
		225/310	3260/4500	300	18	11	10	7,5	1700	3	3	175	56	112	71

## Sectors

Scuba Diving
Fire Brigades
Military
Applications
Naval
Applications

Gas Filling Facilities

Marine

Fish Farms

Please note that information and pictures may be changed or updated without notice, at any time.

