

# W3



## Standard Features

- P61 Purifier with Refillable Purifier Element (Stainless steel)
- High Pressure Particle and Oil Removal Filter (Stainless Steel)
- 2nd and 3rd stages Water Separator (Stainless Steel)
- Intercoolers (Stainless Steel)
- Aftercooler (Stainless Steel)
- Priority Valve (Pressure Maintaining Valve)
- Check Valve
- Electric Panel: YΔ starter
- Canopy Isolated from Subbase for Smoothest Operation
- Auto Drain
- Automatic Start/Stop
- Oil Level Switch
- Removable Filling Panel with 4 Filling Hoses ( Yokes, Filling Valves) and Cylinder Pressure Gauge
- Control Panel: 4 Stage Pressure Gauges, Main Switch, On/Off Buttons, Hourmeter, Test, Reset and Emergency Pushbuttons , 5 Control Leds
- Tropical Cooling with Electric Ventilation Fans
- Air Quality comply with EN 12021

## Optional Features

- Extra Filling Hoses
- Dual Pressure Systems 225-310 Bar/3260-4500 Psi
- Disposable Filter Cartridge
- Electronic Control System

ALKIN Model	Working Pressure		Displacement Capacity			Motor Power		RPM	Stages	Cylinders	Kg.	Dimensions(cm)		
	Bar	Psi	Lt/min	m <sup>3</sup> /h	Cfm	HP	KW					W	L	H
<b>W3-1050</b>	225	3260	1050	63	37	30	22	650	3	3	700	77	111	160
<b>W3-1350</b>	225	3260	1350	81	47,7	40	30	850	3	3	840	77	160	130

## Sectors

- Scuba Diving
- Fire Brigades
- Military Applications
- Naval Applications
- Fish Farms
- Gas Filling Facilities
- Marine

Please note that information and pictures may be changed or updated without notice, at any time.



## ALKIN COMPRESSORS ITALIA

Alkin Compressor exclusive dealer Antonio Persico  
 Tel. 0832-612824 Fax 0832-1791793 Cell. 338-9130100 Email: info@alkinitalia.it  
 www.alkinitalia.it - skype: alkinitalia