

Standard Features

P61 Purifier (stainless steel) with Refillable Purifier Element (stainless steel)

High Pressure Particle and Oil Removel Filter (Stainless Steel)

2nd, 3rd and 4th stages Water Seperator (Stainless Steel)

Intercoolers Aftercooler (Stainless Steel)

Priority Valve (Pressure Maintaining Valve)

Check Valve

Filling Panel with 4 Filling Hoses (Yokes, Filling Valves) and Cylinder Pressure Gauge

Automatic & Manual Drain

Automatic Stop

Oil Level Switch

Control Panel: 4 Stage Pressure Gauges, Main Switch, On/Off Buttons, Hourmeter

Electric Start

Air Quality comply with EN 12021

Optional Features

Extra Filling Hoses Dual Pressure Systems 225-310 Bar/3260-4500 Psi Disposable Fitler Cartridge Electronic Control System

	ALKIN Model	Working Pressure		Displacement Capacity			Motor Power		RPM	Stages	Cylinders	Kg.	Dimensions(cm)		
		Bar	Psi	Lt/min	m³/h	Cfm	НР	KW					w	L	н
1	W4 DIESEL	225/310	3260/4500	600	36	21,2	28,5	-	830	4	3	700	110	195	120



Sectors

Scuba Diving

Fire Brigades

Military

Applications

Naval Applications

Fish Farms

Gas Filling Facilities

Marine

Please note that information and pictures may be changed or updated without notice, at any time.

